

## BORNIT®-Basement Primer

Flat coat for bitumen emulsion coatings



Data sheet: 2006-02-28

Product Description	<b>BORNIT®-Basement Primer</b> is a bitumen emulsion based, solvent-free, non-polluting flat coat for bitumen emulsion coatings an thick bitumen coatings.  The product is certificated by the Testing Institute for Construction Materials, Dresden.	
Area of Application	BORNIT®-Basement Primer is inalienable for the preparation of mineral surfaces in front of processing of BORNIT®- Thick Bitumencoatings 1K, 2K and 2K Flex.  BORNIT®-Basement Primer has good stick properties on concrete, masonry, plaster. It penetrate the building material, bind dust and dry quickly. After drying the flat coat is thin enough to ensure a fast drying of the thick coatings.	
Advantages	<ul> <li>fast drying</li> <li>high penetration into the surface</li> <li>easy application, because the product is ready to use</li> <li>universal use, priming in many cases</li> <li>does not contain solvents</li> <li>better connection between underground and thick coatings</li> </ul>	
Technical data	Type Base Colour Weight Consistency Application Application temperature Storage Storage period	bitumen emulsion bitumen, additives brown-black approx. 1.00 g /cm³ liquid brush, spraying equipment min. +5°C dry and frost-free at least 6 months in unopened packing
Application	All surfaces must be clean, frost-free and free from oil, grease, loosely adhering parts. Any missing sections, damaged concrete or plaster and cracks or openings must be repaired before application.  Do not use BORNIT- foundation bonding primer, if the temperature of the base and the atmosphere is less than +5°C. At normal temperatures, the product is ready to use.  BORNIT®-Basement Primer is applied by using a brush or a spray gun.	
Consumption	approx. 0.2 l/m <sup>2</sup> depending on underground	
Method of delivery	10 I container	75 containers on a pallet45 containers on a pallet18 buckets on a pallet